

summary

residential



Video
Audio

3
23

apartment



Accessibility system

35

commercial



IP intercom
Intercom system IS
Intercom system JP
Intercom system AX
Intercom
Telephony

69
81
87
93
101
117

all markets

Access control
Door locks & accessories
Spare parts
Index

123
127
139
143

For reference

These pictograms are affixed to the products. You can view details, compatibilities and maximum system capacities at a glance.



Important
warning



Available in
3 weeks



Handicapped



Intellectually
challenged



Compatible
stands



Spare parts



Vision
impaired



Hearing
impaired



Capacities

New JP Video Series | INNOVATION

Its technology follows you everywhere!*



Communicate
Protect | Monitor

- Telephone interface (optional)
- Internal communication
- **Video calls from the intercom to your smartphone or tablet ***
- IP interface **compatible** with Apple and Android*



- **Excellent picture quality**
- **Intuitive 7" touchscreen**
- **Hands-free** communication
- 4 door stations + 8 room monitors
- **170° wide angle** camera
- Picture memory
- **SD memory card** (optional)

* subject to the installation of the optional IP interface for smartphones (for JP-4MED: JPTLIIP). Interface sold separately.



Board of choice	4
JP	6
JO	16
Accessories	22










Video residential








Guide

Choose video

There is now an expanded range of kits for the Aiphone residential market. We have many solutions to offer your end customer according to his needs: number of doors, room stations, accessibility, intercom, etc. Please refer to the table below to guide your selection.

		FEATURES			
7-INCH VIDEO SCREEN					
SERIES	REF	MEMORY	DOOR CAPACITY	ROOM STATION CAPACITY	HANDS-FREE
JO TOUCH BUTTON	JOS-1V 		1	2	■
	JOS-1F 		1	2	■
	JO2SDVF 		1	2	■
	JO2SDV 		1	2	■
JP TOUCH SCREEN 	JPS-4AEDV 	■	4	8	■
	JPS-4AEDF 	■	4	8	■



OPTIONS							
 INTERCOM	 VIEWING ANGLE HORIZONTAL/ VERTICAL	 ZOOM	 ACCESS	 VIDEO PROTECTION	 TELEPHONE INTERFACE	 IP INTERFACE	PAGE
	90°/70°						18
	90°/70°						18
	90°/70°						19
	90°/70°						17
■	170°/100°	9 zones	Option	NTSC PAL	■ OR	Smart phone	9
■	170°/100°	9 zones	Option	NTSC PAL	■ OR	Smart phone	18

Les + Aiphone



1.
Magnetic loop
in the handset

2.
7-inch LCD

3.
System status LED
(alarm active, call
in progress, new
pictures)



4.
Zoom
on 9 areas

5.
Hands-free
or handset
communication

6.
Direct access to main functions
(internal call, monitoring, call memory
reading, etc.)

7.
LCD touchscreen

JP Series

Colour video, 7-inch LCD touchscreen, wide angle

COMMUNICATE - MONITOR - PROTECT



Hands-free communication

For greater privacy, the magnetic loop handset can be used while talking.

IP Interface!



The JPTLIIP IP interface builds on the advantages of the room monitor by giving you the option of forwarding all calls from the door station to your smartphone. Receive all your video calls over WiFi, 3G or 4G!

Call forwarding

While talking to the visitor, the call in progress can be forwarded to one of the other 7 monitors in your home.

Internal communication

Inside the house, internal communication can be initiated either via all call on all stations or selectively by choosing a specific monitor only. You can name each monitor (kitchen, bedroom, hallway. etc.) to prevent errors.



JP Series

Colour video, 7-inch LCD touchscreen, wide angle

COMMUNICATE - MONITOR - PROTECT

Video protection

4 cameras can be connected to your system.

Monitoring & babyphone

"MONITORING" allows door stations and installed cameras to be viewed without calling in. Just press a button to switch from one lighting mode to another: day/night. Inside, the master station/sub station pairing provides a reliable baby monitor (no battery, no radio interference, etc.).

Technical alarm

The JP monitors are an indispensable relay that ensures protection of the whole family. The alarm sounds at the maximum volume even if the ring volume is muted.

Emergency call

An emergency call button can be connected to the monitor. When someone activates the alarm in case of illness, it goes off as for an intrusion.

Anti-intrusion alarm

If a sensor is activated, a message appears indicating the identity of the sensor. The red LED flashes and an alarm sounds on all master and sub stations.



JP series kit

7-inch LCD touchscreen

JPS-4AEDV (surface mount)

JPS-4AEDF (flush mount)



Video residential



FEATURES

- Kits are extendable to 7 additional video stations and 3 additional door stations
- **7-inch LCD touchscreen**
- Vandal-resistant, surface mount or flush mount door station, accessibility
- PanTilt mode control, **170° wide angle and zoom on 9 areas** from the camera on the monitor
- Hands-free or handset communication (privacy)
- Picture memory
- RJ45 - CAT5e wiring between room stations
- Optional remote camera (NTSC or PAL)
- Selective call or all call
- Forwarding of call in progress to another sub station
- Door station monitor select for listening
- Monitors can be named (e.g. kitchen, 1st floor, master bedroom, etc.)
- Day/night mode (call volume)

Contents of JPS-4AEDV - JPS-4AEDF kits

	JP-DV	JP-DVF	JP-4MED	PS-2420D
JPS-4AEDV	1		1	1
JPS-4AEDF		1	1	1



JP-DV Vandal-resistant, surface mount door station

OR



JP-DVF Vandal-resistant, flush mount door station

+



JP-4MED
Master station

+



PS-2420D Power supply

DIMENSIONS (mm)






IMAGE VIEW AREA



WIRING



SPECIFICATIONS

Power supply	24 VDC by PS-2420D
Consumption	Max. 390 mA (JP-4MED) Max. 200 mA (JP-4HD)
Communication	Hands-free or handset
Monitor	7-inch colour LCD touchscreen
Door release	Dry closure contact, load breaking capacity 0.5 A 24 VDC or 24 VAC
Wiring	2-wire (+2 wire for door release) in CAT6/RJ45 from master station to the substations (and between sub stations)

Interface

Telephone interface

JPTLI



JPTLI telephone interface!

With the JP range telephone interface, you can answer the door wherever you are.


For added security and peace of mind, you can receive calls from your JP door station on your landline or mobile.

Installation is easy and the interface is compatible with all providers and routers on the market.

Calls can be forwarded to an external number.



DIMENSIONS (mm)




JPTLI

Telephone interface for JP-4MED monitor and JP kits

- 12V power supply included with JPTLI
- Synthesis voice for the door station and telephone
- RJ11 wiring for the station and telephone line
- Output contact activated by the master monitor
- Programmed by DTMF telephone
- Call connection to internal telephone (free)
- Call forwarding to external or mobile number (charged): 1 single number
- Bleep to signal call waiting from door station to telephone during a call
- RJTLI option for connecting 2 telephones to a single line
- **Not compatible with JPTLIIP installation**

N.B. the JPTLI interface takes the place of a sub station and counts towards the total system capacity

WIRING



Interface

IP interface

JPTLIIP



Video residential

Receive video calls from your door station on your smartphone or tablet

With the JP range IP interface, you can answer the door wherever you are.

To increase security and even simulate being at home, you can receive calls from your JP door station on your smartphone or tablet.

Setup is easy. After installation, simply scan a QR code to download the app, then scan another QR

code to pair your smartphone.

2 Smartphones can be connected via JPTLIIP.

The app is only compatible with IOS and Android.



Smartphone



Router or modem with router function




JPTLIIP interface



JPTLIIP

DIMENSIONS (mm)

JPTLIIP




JPTLIIP

IP interface for JP-4MED monitor and JP kits

- 12V power supply included with JPTLIIP
- Audio and video communication
- Requires WIFI, 3G or 4G connection
- Compatible with IOS and Android using the AiphoneJP app
- Synthesis voice for the door station
- RJ45 wiring for the router connection
- Output contact activated by the master monitor
- Simple setup by scanning the QR code linked to JPTLIIP
- Calls to smartphones and tablets ONLY: 2 numbers
- Not compatible with JPTLI installation

N.B. The JPTLIIP interface takes the place of a sub station and counts towards the total system capacity

WIRING



JP Series

7-inch LCD touchscreen

PRESENTATION OF THE SERIES

FEATURES

- Capacity: 4 colour door stations and 8 video monitors
- **7" touchscreen**
- Extra-slim monitor design
- Vandal-resistant, flush or surface mount accessibility door station
- ADJUST button for backlight adjustment
- Monitor-controlled full screen mode, **170° wide angle and 9-zone zoom** function
- **RJ45 wiring - CAT5e or CAT6** between indoor stations in star, series or mixed configuration
- Additional video station (JP-4HD)
- **Optional JPEC cover to blank off the monitor handset**
- Communicate **hands-free** or via the handset for added privacy
- Visual monitoring with audio for 1 minute via monitor button (programmable)
- Picture memory (6 per call) / **storage capacity 1,000 calls on SD card** (not included) / 20 calls on internal station memory
- Options: DVR video signal output, optional alarm contact, exit push button, ringer or detector input, input for connecting 3 foot switches (1 for call control and 2 for the 2 output contacts)
- **Facility for connecting a remote NTSC or PAL camera**
- Selective internal communication to sub station or by broadcast call
- Door station or monitor monitoring (baby phone)
- Transfer ongoing calls to another sub station
- Select which monitors receive door station calls
- Facility for naming monitors (e.g. kitchen, first floor, parents' bedroom, etc.)
- Monitor call selection (selectivity)
- Day / Night mode (sound volume)
- Alarm: PIN code facility (4 digits), facility for programming alarm on / off time, alarm data report

New



SPECIFICATIONS

Power supply	24 VDC by PS-2420D
Consumption	Max. 390 mA (JP-4MED) Max. 200 mA (JP-4HD)
Communication	Hands-free or handset
Monitor	7-inch colour LCD touch screen
Door release	Dry-closure contact, load breaking capacity 0.5 A 24 VDC or 24 VAC
Wiring	2 wires (+ 2 door release wires) in LYT1 8/10th. CAT 5e or CAT6 / RJ45 from the master station to the substations (and between substations)

JP Series

7-inch LCD touchscreen

PRESENTATION OF THE SERIES

4

Doors



8

Rooms

Video residential

OPTIONS



MCWSA
Desk stand



KJKF*
Stainless steel panel
with 100-code back-lit
keypad



RY3-DL
Relay for 2 door
release
controls



AC-10S
Vandal-resistant surface
mount keypad



CFTPJM
Packs of 2 connectors RJ45-
CAT5e / PE in case of an
existing 4 pairs. Delivered with
2 CAT5e / CAT6 cables



IER-2
Call extension



JP-WBA
Long-distance
adaptor and/or
NTSC/PAL interface



JP-8Z
8-direction video
distributor



MGF30
Angle box for JP-DV



TAR4
Relais pour commande
de sonnerie externe



HQW137SNHN
NTSC tube camera
with LED

HQW137SNHP
PAL tube camera
with LED



CRV43H2IRN
NTSC dome
camera with LED

CRV43H2IRP
PAL dome
camera with LED



KJMDVFL**
Stainless steel panel
with 100-code
back-lit keypad
for JP-DVF-L



CISSAL
Hooded surface
mount box for
KJMDVFL



CSJMDVFL
Hooded surface
mount box for
JP-DVF-L



JPTLI
Telephone
interface for JP-4MED




JPTLIIP
Interface IP pour
JP-4MED pour
smartphone

* Camera not included: use JPS-4AEDF kits or JP-DVF door station - ** Camera not included: use JP-DVF-L door station

JPEC

Cover for JP monitor
(blanks off the handset)
Delivered with 1 white and 1 mirror
front cover



JP Series

7-inch LCD touchscreen

PRESENTATION OF THE SERIES

DIMENSIONS (mm)





IMAGE VIEW AREA




ZOOM AND PANTILT MODE

The image coming from the video camera door station can be split into 9 areas. You can then zoom in or out on the monitor, area by area, in PanTilt mode.



WIRING



The + Aiphone



JO SERIES

Video intercom 7-inch extra slim colour screen - IP54 and IK08 door stations

The JO series is equipped with a good definition wide screen 7-inch monitor. Extra slim: only 21 mm thick.

The door stations are vandal-resistant with an IK08 shock rating. Their IP54 protection rating, also allows longer outdoor endurance.

1.

Listening volume

2.

Monitoring

3.

Option button

4.

Screen brightness control

5.

Door release

6.

TALK
OFF

JO series kit

7-screen - IP54 & IK08

JOS-1V • JOS-1F



Content of JOS-1V - JOS-1F kits

	JO-DV	JO-DVF	JO-1MD	PS-1820D
JOS-1V	1		1	1
JOS-1F		1	1	1



JO-DV

Vandal-resistant, surface mount door station

OR



JO-DVF

Vandal-resistant,
flush mount door station

+



JO-1MD

Master station

+



PS-1820D

Power supply

FEATURES

- Expandable kits to 1 additional video station
- **7-inch extra slim monitor: 21 mm thick**
- Brightness screen control
- **2 vandal-resistant door station models: surface mount zinc die-casting model IK08 and IP54, stainless steel flush mount model IK07 and IP54**
- Hands-free communication
- Clear visitor identification provided in colour day and night.
Activation of white LEDs in low-lighting conditions
- 2 door releases

DIMENSIONS (mm)






IMAGE VIEW AREA



WIRING




SPECIFICATIONS

Power supply	18 VDC
Consumption	Max. 400 mA (JO-1MD)
Calling	Chime + image and audio, approx. 45 seconds
Communication	To activate, momentarily press TALK button. Hands-free communication can be activated manually instead of automatically if preferred.
Monitor	7-inch LCD monitor screen
Scanning line	525 lines
Night viewing	High-intensity white LED
Door release	Dry closure contact, load breaking capacity 0.5 A 24 VDC or 24 VAC
Wiring	2-wire (+ 2 wires for door release) 6-wire to sub stations
Distance	Door station to last room station: 50 m (0.6 mmØ) 100 m (0.8 mmØ)

JO series kit

JO2SDV • JO2SDVF



Video residential



FEATURES

- Expandable kits to 1 additional video station
- **7-inch extra slim monitor: 21 mm thick**
- Brightness screen control
- **2-call button door station**, IK07 and IP54, vandal-resistant, stainless steel flush mount
- Hands-free communication
- Clear visitor identification provided in colour day and night.
- Activation of white LEDs in low-lighting conditions
- 2 door releases

Contents of the JO2SDVF & JO2SDV kits

	JO2DV	JO2DVF	JO-1MD	PS-1820D	40781
JO2SDVF		1	2	2	1
JO2SDV	1		2	2	1



or



JO2DVF

Vandal-resistant,
flush mount 2-call
door station

JO2DV

Vandal-resistant,
surface mount
2-call door station

+



2 x JO-1MD Master station

+



2 x PS-1820D
Power supply

+



40781
Power supply

DIMENSIONS (mm)







IMAGE VIEW AREA




WIRING



JO series

Video openers
7-inch screen - IP54 & IK08



PRESENTATION OF THE RANGE

FEATURES

- 1 door station with colour camera
- 2 video stations with 7" screens
- Hands-free communication
- **Extra-slim monitor** (21 mm thick)
- **IK08-rated vandal-resistant surface** or **flush mount door station with IP54 protection rating**
- Colour picture during the day and at night (LED illumination under low light conditions)
- Optional additional sub video station (JO1FD)
- Visual monitoring with audio for 1 minute via monitor button
- Press-to-talk function available
- Additional dry-closure contact for second controlled device



JO-1MD
Master monitor



JO-1FD
Sub-monitor station



JO-DV
Vandal-resistant,
surface mount door
station



JO-DVF
Vandal-resistant,
flush mount door
station



JO2DVF
Vandal-resistant, flush mount
2-call door station,
requires 40781 power supply



JO4DVF
Vandal-resistant, flush mount
4-call door station,
requires 40781 power supply



JO2DV
Vandal-resistant, surface
mount 2 button door station,
requires 40781 power supply



PS-1820D
Power supply



40781
Power supply

OPTIONS



VMKF
Rain hood for JO-DVF



VMK
Rain hood for JO-DV



VVS10
Rain hood for
JO-DV+AC-10S



KJKF*
Stainless steel panel
with 100-code back-lit
keypad



MGF30
Angle box for the
JO-DV



MCWSA
Desk stand with tilt
adjustment



IER-2
Call extension



TAR4
External signalling
relay




AC-10S
Vandal-resistant surface
mount keypad

* Supplied without a camera: requires JOS-1F or JO-DVF door stations

JO series


Video entry
7-inch screen - IP54 & IK08




Video residential

PRESENTATION OF THE RANGE

DIMENSIONS (mm)



WIRING



Accessories

Color video stations

Panel with keypad




KJKF

FEATURES

- 2 mm stainless steel front plates with flush mount back box
- 100-code keypad
- 2 relays
- Power supply reference 40781
- provide JOS-1F kits or JO-DVF panel
- Camera not included

WIRING



Door release adaptor



RY3-DL


FEATURES

- Selective door release control with 1 single button
- The door release selection control is established at the door call-in
- Normally open contact (N/O)
- Normally closed contact (N/C)

Wiring distance 0.6 mmØ 0.8 mmØ

Master to RY3-DL 50 m 100 m

RY3-DL to EL-12S 50 m 100 m




SPECIFICATIONS

Power source 12 - 24 VDC, 30 mA

Power source PS-2420D

Load breaking capacity N/O (normally open) or N/C (normally closed) dry closure contact. 1 A under 50 VAC and 1 A under 30 VDC (for higher consumption, use interface relays)

WIRING




Extension relay



TAR4

DIMENSIONS (mm)




Thickness : 60

FEATURES

- 230 VAC power supply
- Normally open contact (N/O), 5 to 30 sec. timed
- 8-module DIN rail box

WIRING




Call extension



IER-2

DIMENSIONS (mm)



FEATURES

- Call repeater (chime) with adjust cursor
- Indoor installation

WIRING

